

Naaldhulslager

BRI365628-U-IKO - BRI365628-U-IKO

https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/bri365628-u-iko

IKO

MACHINED TYPE NEEDLE ROLLER BEARINGS

With Seal, With Inner Ring, Inch Series



Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)					
Shaft dia. mm (inch)	With two seals		With one seal	d	D	C	B	
57.150 (2 1/4)		BRI 365628 U 980	57.150 (2 1/4)	88.900 (3 1/2)	44.450 (1 3/4)	44.700		
F _w	Standard mounting dimensions (mm)		Basic dynamic load rating C N	Basic static load rating C ₀ N	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring		
	Min.	Max.					Mis.	
69.850 (2 3/4)	65	67	80.7	1.5	98 700	189 000	2 500	LRBZ 364428 B

Notes⁽¹⁾

Minimum allowable value of chamfer dimension r

⁽²⁾

Allowable rotational speed applies to grease lubrication.

Remark⁽¹⁾

The outer ring has an oil groove and an oil hole.

2

Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952382753
Binnendiameter	57.15 mm
Buitendiameter	88.9 mm
Dikte	44.45 mm
Verpakking	1

contact@123kogellager.nl
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE