

Naaldhulslager GBR122016-U-IKO - GBR122016-U-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/gbr122016-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With 6/8e seal		F_w	D	C
19.050 (3/4)	GBR 122016 UU		79	19.050 (3/4)	31.750 (1 1/4)	25.400 (1)
Standard mounting dimensions mm		Seal dynamic load rating C	Ball static load rating C_0	Allowable rotational speed ^(*)		
D_s Max.	r as max (^(†))	N	N	rpm		
27	0.6	26 400	34 500	4 000		

Notes: ^(†) Minimum allowable value of chamfer dimension r .
^(*) Allowable rotational speed applies to grease lubrication.
Remark: This roller ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952382876
Binnendiameter	19.05 mm
Buitendiameter	31.75 mm
Dikte	25.4 mm
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE