

Naaldhulslager GBR243320-UU-IKO - GBR243320-UU-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/gbr243320-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring, Inch Series

| Shaft dia. mm (inch) | Identification number | | Mass (Ref.1) g | Boundary dimensions mm(inch) | | |
|---------------------------------|-----------------------|---------------------------------|----------------------------------|---|--------------|--------------|
| | With two seals | With 6/8e seal | | F_w | D | C |
| 38.100 (1.5) | GBR 243320 UU | | 200 | 38.100(1.5) | 52.388(2.06) | 31.750(1.25) |
| Standard mounting dimensions mm | | Ball dynamic load rating C | Ball static load rating C_0 | Allowable rotational speed ⁽²⁾ | | |
| D_s Max. | r as max (°) | N | N | rpm | | |
| 47.3 | 0.6 | 54 200 | 97 700 | 2 000 | | |

Notes: (1) Minimum allowable value of chamfer dimension r
(2) Allowable rotational speed applies to grease lubrication.
Remark: This roller ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | IKO |
| N° Ean13 | 3663952382999 |
| Binnendiameter | 38.1 mm |
| Buitendiameter | 52.388 mm |
| Dikte | 31.75 mm |
| Verpakking | 1 |

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE