

Naaldhulslager GBR486028-UU-IKO - GBR486028-UU-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/gbr486028-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring, Inch Series

| Shaft dia. mm (inch) | Identification number | | Mass (Ref.) g | Boundary dimensions mm(inch) | | |
|---------------------------------|----------------------------------|---------------------------------|----------------------------------|---|------------|------------|
| | With two seals | With one seal | | F_w | D | C |
| 76.200 (3) | GBR 486028 UU | | 660 | 76.200 (3) | 95.250 (3) | 44.450 (1) |
| Standard mounting dimensions mm | | Seal dynamic load rating C | Ball static load rating C_0 | Allowable rotational speed ^(*) | | |
| D_A Max. | r as max (^(†)) | N | N | rpm | | |
| 88 | 1.5 | 101 000 | 215 000 | 1 100 | | |

Notes: (*) Minimum allowable value of diameter dimension r
(†) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | IKO |
| N° Ean13 | 3663952383163 |
| Binnendiameter | 76.2 mm |
| Buitendiameter | 95.25 mm |
| Dikte | 44.45 mm |
| Verpakking | 1 |

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE