


Naaldhulslager GBR526828-U-IKO - GBR526828-U-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/gbr526828-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		F_w	D	C
82.550 (3 1/4)	GBR 526828 U		960	82.550 (3 1/4)	107.950 (4 1/4)	44.450 (1 3/4)
Standard mounting dimensions mm		Seal dynamic load rating C	Ball diameter d_b	Allowable rotational speed ^(*)		
D_A	r as max	N	N	rpm		
Max.	1.5	127 000	231 000	950		

Notes: (*) Minimum allowable value of diameter dimension r
(**) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952383187
Binnendiameter	82.55 mm
Buitendiameter	107.95 mm
Dikte	44.45 mm
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE