

## Naaldhulslager GBR607632-UU-IKO - GBR607632-UU-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/gbr607632-uu-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, Without Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With 6/8e seal		$F_w$	$D$	$C$
<b>95.250</b> (3 3/4)	<b>GBR 607632 UU</b>		1 320	95.250 (3 3/4)	120.650 (4 7/8)	50.800 (2)
Standard mounting dimensions mm		Seal dynamic load rating $C$	Ball static load rating $C_0$	Allowable rotational speed <sup>(*)</sup> rpm		
$D_A$ Max.	$r$ as max ( <sup>(*)</sup> )	N	N	rpm		
112.6	1.5	175 000	371 000	850		

Notes: (\*) Minimum allowable value of chamfer dimension  $r$   
(\*\*) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952383217
Binnendiameter	95.25 mm
Binnendiameter	3 3/4" inch
Buitendiameter	120.65 mm
Buitendiameter	4 3/4" inch
Dikte	50.8 mm
Dikte	2" inch
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE