

Naaldhulslager GBRI102216-UU-IKO - GBRI102216-UU-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/gbri102216-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		<i>d</i>	<i>D</i>	<i>C</i>
15.875 ($\frac{5}{8}$)	GBRI 102216 UU		127	15.875 ($\frac{5}{8}$)	34.925 ($1\frac{1}{4}$)	25.400 (1)

<i>B</i>	<i>F_w</i>	Standoff mounting dimensions mm			<i>r</i> ⁽¹⁾ Max.	Basic dynamic load rating <i>C</i> N	Basic static load rating <i>C₀</i> N	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring
		Min.	Max.	<i>D_s</i> Max.					
25.650	22.225 ($\frac{7}{8}$)	21	21.2	30	0.6	28 600	40 100	3 500	LRBZ 101416

Notes: (1) Minimum allowable value of chamfer dimension *r*.
(2) Allowable rotational speed applies to grease lubrication.
Remark: This outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952383316
Binnendiameter	15.875 mm
Buitendiameter	34.925 mm
Dikte	25.4 mm
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE