

Naaldhulslager GBRI183020-UU-IKO - GBRI183020-UU-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/gbri183020-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		d	D	C
28.575 (1 1/8)	GBRI 183020 UU		240	28.575 (1 1/8)	47.625 (1 7/8)	31.750 (1 1/4)

B	F _w	Standard mounting dimensions mm		D _s Max.	r _{as max} ⁽¹⁾	Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring
		Min.	Max.						
32.000	34.925 (1 3/8)	33.5	33.9	42.8	0.6	49 500	91 800	2 500	LRBZ 182220

Notes: (1) Minimum allowable value of chamfer dimension r
(2) Allowable rotational speed applies to grease lubrication.
Remark: This outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952383392
Binnendiameter	28.575 mm
Binnendiameter	1 1/8" inch
Buitendiameter	47.625 mm
Buitendiameter	1 7/8" inch
Dikte	31.75 mm
Dikte	1 1/4" inch
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE