

## Naaldhulslager GBRI446828-UU-IKO - GBRI446828-UU-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/gbri446828-uu-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		<i>d</i>	<i>D</i>	<i>C</i>
<b>69.850</b> (2 3/4)	<b>GBRI 446828 UU</b>		1 490	69.850 ± 0.010	107.950 ± 0.010	44.450 ± 0.010

  

<i>B</i>	<i>F<sub>w</sub></i>	Standard mounting dimensions mm			<i>r</i> <sub>as max</sub> <sup>(1)</sup>	Basic dynamic load rating <i>C</i> N	Basic static load rating <i>C<sub>0</sub></i> N	Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring
		<i>d</i> Min.	<i>d</i> Max.	<i>D<sub>s</sub></i> Max.					
44.700	82.550 ± 0.010	77	79	99.9	1.5	127 000	231 000	950	LRBZ 446228

Notes: (1) Minimum allowable value of chamfer dimension *r*.  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952383590
Binnendiameter	69.85 mm
Binnendiameter	2 3/4" inch
Buitendiameter	107.95 mm
Buitendiameter	4 1/4" inch
Dikte	44.45 mm
Dikte	1 3/4" inch
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE