

# Naaldhulslager GBRI527632-UU-IKO - GBRI527632-UU-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/gbri527632-uu-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		$d$	$D$	$C$
<b>82.550</b> (3 1/4)	<b>GBRI 527632 UU</b>		2 010	82.550 (3 1/4)	120.650 (4 7/8)	50.800 (2)

  

$B$	$F_w$	Standard mounting dimensions - mm			$r_{as\ max}$ (1)	Basic dynamic load rating $C$ N	Basic static load rating $C_0$ N	Allowable rotational speed (2) rpm	Assembled inner ring
		Min.	Max.	$D_s$ Max.					
51.050	95.250 (3 3/4)	91	93	112.6	1.5	175 000	371 000	850	<b>LRBZ 526032</b>

Notes: (1) Minimum allowable value of chamfer dimension  $r$ .  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: This outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

## PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952383637
Binnendiameter	82.55 mm
Buitendiameter	120.65 mm
Dikte	50.8 mm
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE