


## Naaldhulslager GBRI608432-U-IKO - GBRI608432-U-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/gbri608432-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)				
	With two seals	With one seal		d	D	C		
<b>95.250</b> (3 7/8)	<b>GBRI 608432 U</b>		2 260	95.250 $\pm 0.010$	133.350 $\pm 0.010$	50.800 $\pm 0.010$		
		Standoff mounting dimensions mm		Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(2)</sup>	Assembled inner ring	
B	F <sub>w</sub>	Min.	Max.	r <sub>as max</sub> <sup>(1)</sup>	N	N	rpm	
51.050	107.950 $\pm 0.010$	103	105	125.3	186 000	419 000	750	<b>LRBZ 606832</b>

Notes: (1) Minimum allowable value of chamfer dimension r.  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: This outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952383668
Binnendiameter	95.25 mm
Buitendiameter	133.35 mm
Dikte	50.8 mm
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE