


## Naaldhulslager NAU4928-IKO - NAU4928-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/nau4928-iko>

**IKO**  
**ROLLER BEARINGS**  
Caged Roller Bearings  
Full Complement Roller Bearings



NAU49 TRU

Shaft dia. mm	Identification number		Mass (Ref.) g	Boundary dimensions mm				
	Full complement type	Caged type		d	D	C	r <sup>(1)</sup> r <sub>s min</sub>	J
140	—	NAU 4928	3 840	140	190	50	2	157.5/176
Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(2)</sup>						
N	N	rpm						
174 000	327 000	2 500						

Note<sup>(1)</sup> Minimum allowable value of chamfer dimension r.  
<sup>(2)</sup> Allowable rotational speed applies to grease lubrication.  
 Remark: This roller ring has an oil groove and an oil hole.  
 2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

## PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952386072
Binnendiameter	140 mm
Binnendiameter	5.512" inch
Buitendiameter	190 mm
Buitendiameter	7.48" inch
Dikte	50 mm
Dikte	1.969" inch
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE