


Naaldhulslager TRU456430-UU-IKO - TRU456430-UU-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/tru456430-uu-iko>

IKO
ROLLER BEARINGS
Caged Roller Bearings [With Seal]
Full Complement Roller Bearings [With Seal]



Shaft dis. mm	Identification number			Mass (Ref.) g	Boundary dimensions mm				
	Full complement type	Caged type			d	D	C	r ⁽¹⁾ min.	J
45	---	---	TRU 456430UU	295	45	64	30	0.6	50.5
E_w	Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed n ₂ rpm						
61	36 400	54 700	2 500						

Notes: (1) Minimum allowable value of chamfer dimension r.
(*) Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.
Remarks: 1. The NAU and NAG series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.
2. The bearings with seals are provided with prepacked grease.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952386171
Binnendiameter	45 mm
Binnendiameter	1.772" inch
Buitendiameter	64 mm
Buitendiameter	2.52" inch
Dikte	30 mm
Dikte	1.181" inch
Gewicht	300 g
Verpakking	1
Standaard	Geen standaard

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE