


## Naaldhulslager NAS5010-ZZ-NR-IKO - NAS5010-ZZ-NR-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/nas5010-zz-nr-iko>

**IKO**  
**ROLLER BEARINGS**  
Roller Bearings for Sheaves



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						
	Sealed type	Shield type		d	D	D <sub>2</sub>	B	C	C <sub>1</sub>	S
50		NAS 5010ZZNR	0.75	50	80	83.8	40	39	30	4.5

f	c	r <sub>s</sub> mm <sup>(1)</sup>	J	Basic dynamic load rating C <sub>0</sub> N	Static load rating C <sub>0</sub> N	Allowable rotational speed <sup>(2)</sup> rpm
2	1.5	0.6	61	100 000	156 000	2 000

Notes<sup>(1)</sup> Minimum allowable value of chamfer dimension r.  
<sup>(2)</sup> Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.  
 Remarks: 1. The NAG and NAU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.  
 2. The bearings with seals are provided with prepacked grease.

## PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952386782
Binnendiameter	50 mm
Buitendiameter	80 mm
Dikte	40 mm
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE