

Naaldhulslager


NAS5013-ZZ-NR-IKO - NAS5013-ZZ-NR-IKO

https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/nas5013-zz-nr-iko



ROLLER BEARINGS

Roller Bearings for Sheaves



Shaft dia. mm	Identification number		Mass (kg)	Boundary dimensions mm						
	Sealed type	Shield type		d	D	D ₂	B	C	C ₁	S
65		NAS 5013ZZNR	1.30	65	100	104.8	46	45	34	5.5

f	c	r _s (1)	J	Basis dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed(2)
		mm		N	N	rpm
2.5	2	0.6	78	128 000	224 000	1 600

Notes(1)

Minimum allowable value of chamfer dimension r

(2)

Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.

Remarks:

The NAG and NAU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.

2: The bearings with seals are provided with prepacked grease.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952386836
Binnendiameter	65 mm
Buitendiameter	100 mm
Dikte	46 mm
Verpakking	1

contact@123kogellager.nl
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE