


Naaldhulslager NAS5015-ZZ-NR-IKO - NAS5015-ZZ-NR-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/nas5015-zz-nr-iko>

IKO
ROLLER BEARINGS
Roller Bearings for Sheaves



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						
	Sealed type	Shield type		d	D	D ₂	B	C	C ₁	S
75		NAS 5015ZZNR	2.00	75	115	119.5	54	53	42	5.5

f	c	r _s mm	J	Basic dynamic load rating C	Static load rating C ₀	Allowable rotational speed ^(*)
				N	N	rpm
2.5	2	0.6	91	179 000	308 000	1 300

Notes^(*) Minimum allowable value of chamfer dimension r.
^(*) Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.
 Remarks: 1. The NAG and NAU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.
 2. The bearings with seals are provided with prepacked grease.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952386874
Binnendiameter	75 mm
Binnendiameter	2.953" inch
Buitendiameter	115 mm
Buitendiameter	4.528" inch
Dikte	54 mm
Dikte	2.126" inch
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE