

Naaldhulslager

NAS5017-UU-NR-IKO - NAS5017-UU-NR-IKO

https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/nas5017-uu-nr-iko



ROLLER BEARINGS

Roller Bearings for Sheaves



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						
	Sealed type	Shield type		d	D	D ₂	B	C	C ₁	S
85	NAS 5017UUNR		2.80	85	130	134.5	60	59	48	5.5

f	c	r _s (1)	J	Basic dynamic load rating C	Static load rating C ₀	Allowable rotational speed(2)
		mm		N	N	rpm
2.5	2	0.6	101	257 000	446 000	1 200

Notes(1)

Minimum allowable value of chamfer dimension r

(2)

Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.

Remarks:

The NAS and NAG series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.

2. The bearings with seals are provided with prepacked grease.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952386928
Binnendiameter	85 mm
Buitendiameter	130 mm
Dikte	60 mm
Verpakking	1

contact@123kogellager.nl
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE