


## Naaldhulslager NAS5024-ZZ-NR-IKO - NAS5024-ZZ-NR-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/nas5024-zz-nr-iko>

**IKO**  
**ROLLER BEARINGS**  
Roller Bearings for Sheaves



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						
	Sealed type	Shield type		d	D	D <sub>2</sub>	B	C	C <sub>1</sub>	S
120		NAS 5024ZZNR	6.95	120	180	188.4	80	79	65	7

f	c	r <sub>s</sub> mm <sup>(1)</sup>	J	Basic dynamic load rating C N	Static load rating C <sub>0</sub> N	Allowable rotational speed <sup>(2)</sup> rpm
3	3	1	139.5	400 000	750 000	850

Notes<sup>(1)</sup> Minimum allowable value of chamfer dimension r  
<sup>(2)</sup> Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.  
 Remarks: 1. The NAS and NAU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.  
 2. The bearings with seals are provided with prepacked grease.

## PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952387000
Binnendiameter	120 mm
Buitendiameter	180 mm
Dikte	80 mm
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE