


Naaldhulslager NAS5028-UU-NR-IKO - NAS5028-UU-NR-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/nas5028-uu-nr-iko>

IKO
ROLLER BEARINGS
Roller Bearings for Sheaves



NAS50-UUNR

Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						
	Sealed type	Shield type		d	D	D ₂	B	C	C ₁	S
140	NAS 5028UUNR		11.0	140	210	218.4	95	94	77	8.5
f	c	r _s mm ⁽¹⁾	J	Basic dynamic load rating C N	Static load rating C ₀ N	Allowable rotational speed ⁽²⁾ rpm				
3	3	1	167	543 000	1 070 000	700				

Notes^(*)
⁽¹⁾ Minimum allowable value of chamfer dimension r
⁽²⁾ Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.
 Remarks: 1. The NAS and NAU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.
 2. The bearings with seals are provided with prepacked grease.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952387055
Binnendiameter	140 mm
Buitendiameter	210 mm
Dikte	95 mm
Gewicht	800 g
Verpakking	-
Standaard	Geen standaard

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE