

Naaldhulslager

NAS5034-UU-NR-IKO - NAS5034-UU-NR-IKO

https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/nas5034-uu-nr-iko



ROLLER BEARINGS

Roller Bearings for Sheaves



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						
	Sealed type	Shield type		d	D	D ₂	B	C	C ₁	S
170	NAS 5034UU	NR	22.5	170	260	270	122	121	99	11

f	c	r _s (1)	J	Basic dynamic load rating C	Static load rating C ₀	Allowable rotational speed (2)
				N	N	rpm
4	3.5	1.5	204.5	857 000	1 730 000	800

Notes (1)

Minimum allowable value of chamfer dimension r

(2)

Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.

Remarks 1:

The NAS and NAG series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.

2:

The bearings with seals are provided with prepacked grease.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952387109
Binnendiameter	170 mm
Buitendiameter	260 mm
Dikte	122 mm
Verpakking	1

contact@123kogellager.nl
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE