

Naaldhulslager NAX6040Z-IKO - NAX6040Z-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/nax6040z-iko>

IKO

COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing Without Inner Ring
Needle Roller Bearings with Thrust Roller Bearing Without Inner Ring

Identification number										
Shaft dia. mm	Mass (Ref.) g		With dust cover		Mass (Ref.) g		Mass (Ref.) g		With dust cover	
	60	NAX 6040Z		454		---		---		---
Boundary dimensions mm										
F_w	D	D_1	D_2	L	H	r_1	r_2	d_1	d_2	Basic dynamic load rating C
60	72	85	86.5	40	17	12	1	60	75	47 500
Basic static load rating C_0										
Allowable rotational speed ⁽²⁾										
Radial										41 400
Axial										103 000
Radial										89 700
Axial										4 000

Notes: (1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Grease is not prepacked. Perform proper lubrication.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952390376
Binnendiameter	60 mm
Buitendiameter	72 mm
Dikte	40 mm
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE