

## Naaldhulslager NBX6040Z-IKO - NBX6040Z-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/nbx6040z-iko>

**IKO**  
**COMBINED TYPE NEEDLE ROLLER BEARINGS**  
Needle Roller Bearings with Thrust Ball Bearing Without Inner Ring  
Needle Roller Bearings with Thrust Roller Bearing Without Inner Ring

Identification number														
Shaft dia. mm	Mass (Ref.) g		With dust cover		Mass (Ref.) g		Mass (Ref.) g		With dust cover					
60	---	---	---	---	---	---	---	---	---	---				
NBX 6040Z 538														
Boundary dimensions mm							Basic dynamic load rating C		Basic static load rating C <sub>0</sub>		Allowable rotational speed <sup>(2)</sup> rpm			
F <sub>w</sub>	D	D <sub>1</sub>	D <sub>2</sub>	L	H	r <sub>s</sub> min.	Radial	Axial	Radial	Axial				
60	72	85	86.5	40	17	12	1	60	82	47 500	64 600	103 000	224 000	4 000

Notes: <sup>(1)</sup> Minimum allowable value of chamfer dimension r. <sup>(2)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NBX series.  
Remarks: 1. The outer ring has an oil groove and an oil hole. 2. Grease is not prepacked. Perform proper lubrication.

## PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952390529
Binnendiameter	60 mm
Buitendiameter	72 mm
Dikte	40 mm
Verpakking	1
Standaard	Geen standaard

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE