

Naaldhulslager NAXI923-IKO - NAXI923-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/naxi923-iko>

UNIDIRECTIONAL TYPE NEEDLE ROLLER BEARINGS

Needle Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Bearings with Thrust Roller Bearing **With Inner Ring**

Identification number

	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g	d
NAXI 923	49.5	—	—	—	—	—	9

Boundary dimensions mm		Shoulder diameter mm	Basic dynamic load rating C		Basic static load rating C ₀		Allowable rotational speed ⁽¹⁾	Assemble						
B	H	I ₁	r _{min}	r _{max}	Radial	Axial	Radial	Axial	rpm					
16	9	6.5	0.3	0.3	12	12	20	11	9 250	9 670	11 200	11 100	9 000	LRT

(1) Minimum allowable value of chamfer dimension r. Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in IAX series, and a maximum of 25% of this value is allowable in the NEX series. The outer ring has an oil groove and an oil hole. Grease is not prepacked. Perform proper lubrication.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952390666
Binnendiameter	9 mm
Buitendiameter	21 mm
Dikte	23 mm
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE