

Naaldhulslager NAXI1223-IKO - NAXI1223-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/naxi1223-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Identification number																	
Shaft dia. mm	Mass (Ref.) g		With dust cover		Mass (Ref.) g		With dust cover		Mass (Ref.) g		Assembled inner ring						
	12	NAXI 1223	55.5	—	—	—	—	—	—	12 24 28							
Boundary dimensions mm																	
D_2	L	B	H	I_1	r	d_1	d_2	d_3	Radial	Axial	Radial	Axial	Allowable rotational speed ⁽²⁾ rpm	LRT 71016			
25	23	16	9	6.5	0.3	0.2	10	10	18	9	8	230	10 000	9 190	11 100	9 500	LRT 71016

Notes:
(1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.

Remarks:
1. The outer ring has an oil groove and an oil hole.
2. Grease is not prepacked. Perform proper lubrication.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952390680
Binnendiameter	12 mm
Buitendiameter	24 mm
Dikte	23 mm
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE