

Naaldhulslager NBXI1425Z-IKO - NBXI1425Z-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/nbxi1425z-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Identification number														
Shaft dia. mm	Mass (Ref.) g		With dust cover		Mass (Ref.) g		With dust cover		Mass (Ref.) g		d	D	D ₁	
	14	—	—	—	—	—	—	—	—	—				NBXI 1425Z
Boundary dimensions mm														
D ₂	L	B	H	I ₁	r ⁽¹⁾	r ⁽²⁾	d ₄	d ₅	d	d ₁	d ₂	d ₃	Assembled inner ring	
31	25	17	9	8	0.3	0.3	17	17	28	16	12	900	11 400	
Basic dynamic load rating C														
Basic static load rating C ₀														
Allowable rotational speed ⁽³⁾														
											rpm	LRT 141717		

Notes:
(1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NBX series.
Remarks:
Z: The outer ring has an oil groove and an oil hole.
2: Grease is not prepacked. Perform proper lubrication.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952390758
Binnendiameter	14 mm
Buitendiameter	26 mm
Dikte	25 mm
Gewicht	50 g
Verpakking	-
Standaard	Geen standaard

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE