

# Naaldhulslager NBXI3030-IKO - NBXI3030-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/nbxi3030-iko>

**IKO**  
**COMBINED TYPE NEEDLE ROLLER BEARINGS**

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**  
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Shaft dia. mm	Identification number						d	D	D <sub>i</sub>
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g			
30	---	---	<b>NBXI 3030</b>	<b>225</b>	---	---	30	47	52

Boundary dimensions mm				Bore chamfer mm	Bore chamfer mm	Basic dynamic load rating C		Basic static load rating C <sub>0</sub>		Allowable rotational speed <sup>(1)</sup> rpm	Assembled inner ring LRT 303520				
D <sub>2</sub>	L	B	H			Radial	Axial	Radial	Axial						
53	30	20	12	9	0.6	0.3	35	50	34	26 900	29 100	46 200	91 100	7 000	LRT 303520

Notes:  
(1) Minimum allowable value of chamfer dimension r.  
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.  
Remarks:  
1. The outer ring has an oil groove and an oil hole.  
2. Grease is not prepacked. Perform proper lubrication.

## PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952390901
Binnendiameter	30 mm
Buitendiameter	47 mm
Dikte	30 mm
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE