

Naaldhulslager NBXI3532-IKO - NBXI3532-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/nbxi3532-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Shaft dia. mm	Identification number						d	D	D _i
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g			
35	---	---	---	NBXI 3532	286	---	35	52	60

Boundary dimensions mm			Lead-in chamfer mm	Lead-in chamfer mm	Basic dynamic load rating C		Basic static load rating C ₀		Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring						
D ₂	L	H			Radial	Axial	Radial	Axial								
61	32	20	13	10	0.6	0.3	40	40	57	39	29 400	41 700	54 100	133 000	6 000	LRT 354020

Notes⁽¹⁾ Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Grease is not prepacked. Perform proper lubrication.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952390949
Binnendiameter	35 mm
Binnendiameter	1.378" inch
Buitendiameter	52 mm
Buitendiameter	2.047" inch
Dikte	32 mm
Dikte	1.26" inch
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE