

# Naaldhulslager NBXI4032-IKO - NBXI4032-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/nbxi4032-iko>

**IKO**  
**COMBINED TYPE NEEDLE ROLLER BEARINGS**

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**  
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Shaft dia. mm	Identification number								d	D	D <sub>i</sub>
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g					
40	---	---	---	<b>NBXI 4032</b>	344	---	---	---	40	58	65

Boundary dimensions mm				Bearing series	Basic dynamic load rating C	Basic static load rating C <sub>0</sub>		Allowable rotational speed <sup>(1)</sup> rpm	Assembled inner ring						
D <sub>2</sub>	L	B	H			Radial	Axial			Radial	Axial				
66.5	32	20	14	9	0.6	0.3	45	62	44	31 000	40 800	60 200	133 000	5 500	LRT 404520

Notes<sup>(1)</sup> Minimum allowable value of chamfer dimension r.  
<sup>(2)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NBX series.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. Grease is not prepacked. Perform proper lubrication.

## PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952390987
Binnendiameter	40 mm
Buitendiameter	58 mm
Dikte	32 mm
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE