

Naaldhulslager NBXI4535Z-IKO - NBXI4535Z-IKO

<https://www.123kogellager.nl/kogellager-behuizing/naaldlager/naaldhulslager/nbxi4535z-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Shaft dia. mm	Identification number										d	D	D _i	
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g	NBXI 4535Z							
45	---	---	---	---	---	---	NBXI 4535Z				396	45	62	70

Boundary dimensions mm				Lead-in chamfer mm	Lead-in chamfer mm	Basic dynamic load rating C		Basic static load rating C ₀		Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring LRT 455025									
D ₂	L	B	H			Radial	Axial	Radial	Axial											
71.5	35	25	14	10	0.6	0.3	50	67	49	42	200	43	300	83	400	148	000	5	000	LRT 455025

Notes:
(1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NBX series.

Remarks:
Z: The outer ring has an oil groove and an oil hole.
2: Grease is not prepacked. Perform proper lubrication.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952391038
Binnendiameter	45 mm
Buitendiameter	62 mm
Dikte	35 mm
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE