


GE Stangkop GE90ES-2RS-IKO - GE90ES-2RS-IKO

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/ge/ge90es-2rs-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (ref.) kg	Boundary dimensions mm						Permissible tilting angle degree			
	Without seals	With seals		d	D	B	C	d_s	r_1 (1)	r_2 (1)	α	α_1	
90		GE 90ES-2RS	2.82	90	130	60	50	115	1	1	5	3	
Mounting dimensions mm		Dynamic load capacity C_d		Static load capacity C_s									
d_s		D_s		N		N							
Min.	Max.(2)	Max.	Min.	N		N							
95.5	98	124.5	112	564 000		3 380 000							

Notes (1) Minimum allowable value of chamfer dimensions r_1 and r_2 .
 (2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s .
 Remark 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
 2. Not provided with prepacked grease. Perform proper lubrication for use.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952391939
Binnendiameter	90 mm
Buitendiameter	130 mm
Dikte	60 mm
Type	GE
Smering	zonder
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE