


GE Stangkop GE260ES-2RS-IKO - GE260ES-2RS-IKO

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/ge/ge260es-2rs-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (ref.) kg	Boundary dimensions mm						Permissible tilting angle degree		
	Without seals	With seals		d	D	B	C	d_s	r_1 (1)	r_2 (1)	α	α_1
260		GE 260ES-2RS	52.0	260	370	150	110	325	1.1	1.1	7	6
Mounting dimensions mm		Dynamic load capacity C_d		Static load capacity C_s								
d_s		D_s		N		N						
Min.	Max.(2)	Max.	Min.									
267	288	363	320	3 510 000		21 000 000						

Notes(1)
(1) Minimum allowable value of chamfer dimensions r_1 and r_2
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s .

Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952392134
Binnendiameter	260 mm
Buitendiameter	370 mm
Dikte	150 mm
Type	GE
Smering	zonder
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE