


## GE Stangkop GE280ES-IKO - GE280ES-IKO

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/ge/ge280es-iko>

**IKO**  
**SPHERICAL BUSHINGS**  
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm					Permissible tilting angle degree			
	Without seals	With seals		$d$	$D$	$B$	$C$	$d_s$	$r_1$ (1)	$r_2$ (1)	$\alpha$	$\alpha_1$
<b>280</b>	<b>GE 280ES</b>		<b>66.0</b>	<b>280</b>	<b>400</b>	<b>155</b>	<b>120</b>	<b>350</b>	<b>1.1</b>	<b>1.1</b>	<b>6</b>	<b>5</b>
Mounting dimensions mm			Dynamic load capacity $C_d$ N	Static load capacity $C_s$ N								
$d_s$	$D_s$											
Min.	Max.(2)	Max.	Min.									
<b>287</b>	<b>313.5</b>	<b>393</b>	<b>345</b>	<b>4 120 000</b>	<b>24 700 000</b>							

Notes (1) Minimum allowable value of chamfer dimensions  $r_1$  and  $r_2$ .  
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of  $d_s$ .  
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.  
2. Not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952392158
Binnendiameter	280 mm
Buitendiameter	400 mm
Dikte	155 mm
Type	GE
Smering	zonder
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE