

GE Stangkop GE300ES-IKO - GE300ES-IKO

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/ge/ge300es-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree		
	Without seals	With seals		d	D	B	C	d_s	r_1 (1)	r_2 (1)	α	α_1
300	GE 300ES		76.0	300	430	165	120	375	1.1	1.1	7	6
Mounting dimensions mm			Dynamic load capacity C_d N	Static load capacity C_s N								
d_s	D_s				Min.	Max. (2)	Min.	Max.	Min.	Max.	Min.	Max.
307	336.5	423	371	4 410 000	26 500 000							

Notes (1) Minimum allowable value of chamfer dimensions r_1 and r_2 .
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s .
Remark 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952392165
Binnendiameter	300 mm
Buitendiameter	430 mm
Dikte	165 mm
Type	GE
Smering	zonder
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE