

## GE Stangkop GE80GS-IKO - GE80GS-IKO

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/ge/ge80gs-iko>

**IKO**  
**SPHERICAL BUSHINGS**  
Steel-on-steel Spherical Bushings

Shaft dia. mm	Identification number		Mass (ref.) kg	Boundary dimensions mm						Permissible tilting angle degree		
	Without seals	With seals		d <sub>s</sub>	D	B	C	d <sub>s</sub>	r <sub>1</sub> (1)		r <sub>2</sub> (1)	α
<b>80</b>	<b>GE 80GS</b>		<b>3.60</b>	<b>80</b>	<b>130</b>	<b>75</b>	<b>50</b>	<b>115</b>	<b>1</b>	<b>1</b>	<b>14</b>	<b>13</b>
Mounting dimensions mm		Dynamic load capacity C <sub>d</sub> N	Static load capacity C <sub>s</sub> N	d <sub>s</sub>		D <sub>s</sub>						
Min.	Max.(2)			Max.	Min.	Max.	Min.	Max.				
85.5	87	124.5	112	564 000	3 380 000							

Notes(1) Minimum allowable value of chamfer dimensions r<sub>1</sub> and r<sub>2</sub>.  
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d<sub>s</sub>.  
Remark1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.  
2. Not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952392462
Binnendiameter	80 mm
Buitendiameter	130 mm
Dikte	75 mm
Type	GE
Smering	zonder
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE