


GE Stangkop GE110GS-2RS-IKO - GE110GS-2RS-IKO

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/ge/ge110gs-2rs-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (ref.) kg	Boundary dimensions mm						Permissible tilting angle degree		
	Without seals	With seals		d	D	B	C	d_s	r_1 (1)	r_2 (1)	α	α_1
110		GE 110GS-2RS	9.70	110	180	100	70	160	1	1	12	11
Mounting dimensions mm		Dynamic load capacity C_d		Static load capacity C_s								
d_s	D_s	C_d	C_s									
Min. Max.(2)	Max. Min.	N	N									
115.5	124.5 174.5	154	1 100 000	6 590 000								

Notes (1) Minimum allowable value of chamfer dimensions r_1 and r_2 .
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s .
Remark: The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952392523
Binnendiameter	110 mm
Buitendiameter	180 mm
Dikte	100 mm
Type	GE
Smering	zonder
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE