

GE Stangkop GE120GS-IKO - GE120GS-IKO

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/ge/ge120gs-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings

Shaft dia. mm	Identification number		Mass (ref.) kg	Boundary dimensions mm						Permissible tilting angle degree		
	Without seals	With seals		d_s	D	B	C	d_s	r_1 (1)	r_2 (1)	α	α_1
120	GE 120GS		15.5	120	210	115	70	180	1	1	16	15
Mounting dimensions mm		Dynamic load capacity C_d		Static load capacity C_s								
d_s		D_s		N		N						
Min.	Max.(2)	Max.	Min.									
125.5	138.5	204.5	176	1 240 000		7 410 000						

Notes (1) Minimum allowable value of chamfer dimensions r_1 and r_2 .
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s .
Remark 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952392547
Binnendiameter	120 mm
Buitendiameter	210 mm
Dikte	115 mm
Type	GE
Smering	zonder
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE