

GE Stangkop GE140GS-2RS-IKO - GE140GS-2RS-IKO

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/ge/ge140gs-2rs-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (ref.) kg	Boundary dimensions mm						Permissible tilting angle degree			
	Without seals	With seals		d	D	B	C	d_s	r_1 (1)	r_2 (2)	α	α_1	
140		GE 140GS-2RS	19.2	140	230	130	80	200	1	1	16	15	
Mounting dimensions mm		Dynamic load capacity C_d		Static load capacity C_s									
d_s		D_s		N		N							
Min.	Max. (2)	Max.	Min.	N		N							
145.5	152	224.5	195	1 570 000		9 410 000							

Notes (1) Minimum allowable value of chamfer dimensions r_1 and r_2 .
 (2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s .
 Remark 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
 2. Not provided with prepacked grease. Perform proper lubrication for use.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952392561
Binnendiameter	140 mm
Binnendiameter	5.512" inch
Buitendiameter	230 mm
Buitendiameter	9.055" inch
Dikte	130 mm
Dikte	5.118" inch
Type	GE
Smering	zonder
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE