

GE Stangkop GE160GS-IKO - GE160GS-IKO

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/ge/ge160gs-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings

Shaft dia. mm	Identification number		Mass (ref.) kg	Boundary dimensions mm						Permissible tilting angle degree		
	Without seals	With seals		d_s	D	B	C	d_s	r_1 (1)	r_2 (1)	α	α_1
160	GE 160GS		25.4	160	260	135	80	225	1	1.1	16	14
Mounting dimensions mm			Dynamic load capacity C_d N	Static load capacity C_s N								
d_s		D_s										
Min.	Max.(2)	Max.	Min.									
165.5	180	253	221	1 770 000		10 600 000						

Notes(1) Minimum allowable value of chamfer dimensions r_1 and r_2 .
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s .
Remark1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952392585
Binnendiameter	160 mm
Buitendiameter	260 mm
Dikte	135 mm
Type	GE
Smering	zonder
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE