

GE Stangkop GE180GS-IKO - GE180GS-IKO

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/ge/ge180gs-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (ref.) kg	Boundary dimensions mm						Permissible tilting angle degree		
	Without seals	With seals		d	D	B	C	d_s	r_1 ⁽¹⁾	r_2 ⁽¹⁾	α	α_1
180	GE 180GS		34.7	180	290	155	100	250	1.1	1.1	14	13
Mounting dimensions mm			Dynamic load capacity C_d N	Static load capacity C_s N								
d_s		D_s										
Min.	Max. ⁽²⁾	Max.	Min.									
187	196	283	244	2 450 000		14 700 000						

Notes⁽¹⁾ Minimum allowable value of chamfer dimensions r_1 and r_2 .
⁽²⁾ When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s .
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952392592
Binnendiameter	180 mm
Buitendiameter	290 mm
Dikte	155 mm
Type	GE
Smering	zonder
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE