


GE Stangkop GE200GS-2RS-IKO - GE200GS-2RS-IKO

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/ge/ge200gs-2rs-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (ref.) kg	Boundary dimensions mm						Permissible tilting angle degree		
	Without seals	With seals		d	D	B	C	d_s	r_1 (1)	r_2 (1)	α	α_1
200		GE 200GS-2RS	43.9	200	320	165	100	275	1.1	1.1	15	14
Mounting dimensions mm		Dynamic load capacity C_d N	Static load capacity C_s N	d_s		D_s		r_1		r_2		
Min.	Max. (2)			Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	
207	220	313	289	2 700 000	16 200 000							

Notes (1) Minimum allowable value of chamfer dimensions r_1 and r_2 .
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s .
Remark 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952392615
Binnendiameter	200 mm
Buitendiameter	320 mm
Dikte	165 mm
Type	GE
Smering	zonder
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE