

# GE Stangkop

## GE220GS-2RS-IKO - GE220GS-2RS-IKO

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/ge/ge220gs-2rs-iko>

**IKO**  
**SPHERICAL BUSHINGS**  
Steel-on-steel Spherical Bushings

Shaft dia. mm	Identification number		Mass (ref.) kg	Boundary dimensions mm						Permissible tilting angle degree		
	Without seals	With seals		$d$	$D$	$B$	$C$	$d_s$	$r_1$ (1)	$r_2$ (1)	$\alpha$	$\alpha_1$
<b>220</b>		<b>GE 220GS-2RS</b>	<b>51.3</b>	<b>220</b>	<b>340</b>	<b>175</b>	<b>100</b>	<b>300</b>	<b>1.1</b>	<b>1.1</b>	<b>16</b>	<b>14</b>

  

Mounting dimensions mm				Dynamic load capacity $C_d$ N	Static load capacity $C_s$ N
$d_s$	$D_s$	Min.	Max. (2)		
Min.	Max. (2)	Max.	Min.		
227	243.5	333	296	2 940 000	17 700 000

Notes (1) Minimum allowable value of chamfer dimensions  $r_1$  and  $r_2$ .  
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of  $d_s$ .  
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.  
2. Not provided with prepacked grease. Perform proper lubrication for use.

## PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952392646
Binnendiameter	220 mm
Buitendiameter	340 mm
Dikte	175 mm
Type	GE
Smering	zonder
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE