

GE Stangkop SBB60-2RS-IKO - SBB60-2RS-IKO

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/ge/sbb60-2rs-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) kg	Boundary dimensions mm(inch)			
	Without seal	With seals		d	D	B	C
95.250 (3 7/8)		SBB 60-2RS	6.87	95.250 (3 7/8)	149.225 (5 7/8)	83.34 (3.281)	71.42 (2.812)
Radial internal clearance mm Min./Max.	Mounting dimensions mm		Dynamic load capacity C _d N	Static load capacity C _s N			
	d _k	d ₁ r ₁ max. r ₂ max.					
137 (5.394)	0.13 / 0.23	108.4 0.6 0.8	960 000	5 760 000			

Notes: (1) Minimum allowable value of chamfer dimensions r₁ and r₂.
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_k.
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952392998
Binnendiameter	95.25 mm
Binnendiameter	3 3/4" inch
Buitendiameter	149.225 mm
Buitendiameter	5 7/8" inch
Dikte	83.34 mm
Dikte	3 9/32" inch
Type	GE
Smering	zonder
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE