

## GE Stangkop SBB68-IKO - SBB68-IKO

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/ge/sbb68-iko>

**IKO**  
**SPHERICAL BUSHINGS**  
Steel-on-steel Spherical Bushings Inch Series

Shaft dia. mm (inch)	Identification number		Mass (Ref.) kg	Boundary dimensions mm(inch)			
	Without seal	With seals		d	D	B	C
<b>107.950</b> (4 1/4)	<b>SBB 68</b>		<b>8.46</b>	<b>107.950</b> (4 1/4)	<b>168.275</b> (6 5/8)	<b>94.46</b> (3.719)	<b>80.95</b> (3.187)
Radial internal clearance mm Min./Max.	Mounting dimensions mm		Dynamic load capacity C <sub>d</sub> N	Static load capacity C <sub>s</sub> N			
	d <sub>k</sub>	d <sub>1</sub> r <sub>1</sub> max. r <sub>2</sub> max.					
155(6.102)	0.13 / 0.23 122.6 0.8 1.1		1 230 000	7 380 000			

Notes: (1) Minimum allowable value of chamfer dimensions r<sub>1</sub> and r<sub>2</sub>.  
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d<sub>k</sub>.  
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.  
2. Not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952393025
Binnendiameter	107.95 mm
Buitendiameter	168.275 mm
Dikte	94.46 mm
Type	GE
Smering	zonder
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE