

GE Stangkop SBB68-2RS-IKO - SBB68-2RS-IKO

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/ge/sbb68-2rs-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings Inch Series

| Shaft dia. mm (inch) | Identification number | | Mass (flat) kg | Boundary dimensions mm(inch) | | | |
|--|---------------------------|--|--|---|-----------------|--------------|--------------|
| | Without seal | With seals | | d | D | B | C |
| 107.950 (4 1/4) | | SBB 68-2RS | 8.46 | 107.950 (4 1/4) | 168.275 (6 5/8) | 94.46(3.719) | 80.95(3.187) |
| Radial internal clearance mm Min./Max. | Mounting dimensions mm | | Dynamic load capacity C _d N | Static load capacity C _s N | | | |
| | d _k | d ₁ r ₁ max. r ₂ max. | | | | | |
| 155(6.102) | 0.13 / 0.23 | 122.6 0.8 1.1 | 1 230 000 | 7 380 000 | | | |

Notes: (1) Minimum allowable value of chamfer dimensions r₁ and r₂.
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_k.
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | IKO |
| N° Ean13 | 3663952393032 |
| Binnendiameter | 107.95 mm |
| Buitendiameter | 168.275 mm |
| Dikte | 94.46 mm |
| Type | GE |
| Smering | zonder |
| Verpakking | 1 |

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE