

GE Stangkop SBB96-2RS-IKO - SBB96-2RS-IKO

<https://www.123kogellager.nl/kogellager-behuizing/stangkop/ge/sbb96-2rs-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings Inch Series

Shaft dia. mm (inch)	Identification number		Mass (Ref.) kg	Boundary dimensions mm(inch)			
	Without seal	With seals		d	D	B	C
152.400 (6)		SBB 96-2RS	17.6	152.400 (6)	222.250 (8 7/8)	120.65(4.750)	104.78(4.125)
Radial internal clearance mm Min./Max.	Mounting dimensions mm		Dynamic load capacity C _d N	Static load capacity C _s N			
	d _k	d ₁ r ₁ max. r ₂ max.		C _d	C _s		
207(8.150)	0.13 / 0.23	167.5 0.8 1.1	2 130 000	12 800 000			

Notes: (1) Minimum allowable value of chamfer dimensions r₁ and r₂.
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_k.
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3663952393117
Binnendiameter	152.4 mm
Buitendiameter	222.25 mm
Dikte	120.65 mm
Type	GE
Smering	zonder
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE