

Nokrollen CFE16-UU-IKO - CFE16-UU-IKO

<https://www.123kogellager.nl/kogellager-behuizing/kogellager/nokrollen/cfe16-uu-iko>

IKO

CAM FOLLOWERS

Eccentric Type Cam Followers With Cage/With Screwdriver Slot



Outside diameter of eccentric roller mm	Identification number				Mass (Ref.)								
	Shield type		Sealed type		ϕ	D	C	d_2					
22	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring	CFE 16	UU	190	35	18	22			
Boundary dimensions mm													
G	B ₃	B ₁ max	B ₂ max	B ₂	C ₁	G ₁	ϕ (1)	Mounting dimension f Min. mm	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N	
M16×1.5	15.5	19.6	52.1	32.5	0.8	6	17	0.6, 0.8	26	58.5	12 000	18 300	18 300

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3616060459985
Binnendiameter	22 mm
Binnendiameter	0.866" inch
Buitendiameter	35 mm
Buitendiameter	1.378" inch
Dikte	18 mm
Dikte	0.709" inch
Gewicht	190 g
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE