


# Nokrollen CFE30-2-UU-IKO - CFE30-2-UU-IKO

<https://www.123kogellager.nl/kogellager-behuizing/kogellager/nokrollen/cfe30-2-uu-iko>

**IKO**

**CAM FOLLOWERS**

Eccentric Type Cam Followers With Cage/With Screwdriver Slot



Outside diameter of eccentric roller mm	Identification number						Mass (Ref.)			
	Shield type			Sealed type			Ø	D	C	d <sub>2</sub>
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With crowned outer ring	With cylindrical outer ring	CFE 30-2 UU				
<b>41</b>							2 380	90	35	41

Boundary dimensions mm										Essentiality g	Mounting dimension f mm	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N	Maximum allowable static load N
G	B <sub>3</sub>	B max	B <sub>1</sub> max	B <sub>2</sub>	C <sub>1</sub>	G <sub>1</sub>	(1) r <sub>max</sub>	e	g						
M30×1.5	32.5	37	100	63	1	8	30.5	1	1.5	49	438	45 400	85 100	85 100	

## PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3616060460257
Binnendiameter	41 mm
Buitendiameter	90 mm
Dikte	35 mm
Gewicht	2380 g
Verpakking	1

[contact@123kogellager.nl](mailto:contact@123kogellager.nl)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE