

Nokrollen CFE16-VR-IKO - CFE16-VR-IKO

<https://www.123kogellager.nl/kogellager-behuizing/kogellager/nokrollen/cfe16-vr-iko>

IKO
CAM FOLLOWERS

Eccentric Type Cam Followers **Full Complement Type/With Screwdriver Slot**

| Outside diameter of eccentric roller mm | Identification number | | | | Mass (Ref.) | | | |
|--|-------------------------|-----------------------------|-------------------------|-----------------------------|-------------|----|----|----|
| | Shield type | | Sealed type | | g | D | C | da |
| | With crowned outer ring | With cylindrical outer ring | With crowned outer ring | With cylindrical outer ring | | | | |
| 22 | CFE 16 | VR | | | 193 | 35 | 18 | 22 |

| Boundary dimensions mm | | | | | | | | | | |
|------------------------|----------------|------------------|-------------------|----------------|----------------|----------------|----------------|-------------------|-----|----|
| G | B ₃ | B _{max} | B _{1max} | B ₂ | C ₁ | g ₁ | G ₁ | r _{1min} | E | f |
| M16 × 1.5 | 15.5 | 19.6 | 52.1 | 32.5 | 0.8 | 6 | 17 | 0.6 | 0.8 | 26 |

| Mounting dimension | Maximum operating torque | Basic dynamic load rating | Basic static load rating | Maximum allowable static load |
|--------------------|--------------------------|---------------------------|--------------------------|-------------------------------|
| f Min. mm | N·m | C | C ₀ | N |
| 26 | 58.5 | 20 700 | 37 600 | 23 200 |

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | IKO |
| N° Ean13 | 3616060461094 |
| Binnendiameter | 22 mm |
| Buitendiameter | 35 mm |
| Dikte | 18 mm |
| Gewicht | 193 g |
| Verpakking | 1 |

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE