

Nokrollen CFE16-VUUR-IKO - CFE16-VUUR-IKO

<https://www.123kogellager.nl/kogellager-behuizing/kogellager/nokrollen/cfe16-vuur-iko>

IKO
CAM FOLLOWERS
Eccentric Type Cam Followers Full Complement Type/With Screwdriver Slot

| Outside diameter of eccentric roller mm | Identification number | | | | Mass (Ref.) | | | |
|--|-------------------------|-----------------------------|-------------------------|-----------------------------|-------------|-----------|-----------|----------------|
| | Shield type | | Sealed type | | g | D | C | d _e |
| | With crowned outer ring | With cylindrical outer ring | With crowned outer ring | With cylindrical outer ring | | | | |
| 22 | | | | | 193 | 35 | 18 | 22 |
| CFE 16 VUUR | | | | | | | | |

| Boundary dimensions mm | | | | | | | | | | |
|------------------------|----------------|------------------|-------------------------------|----------------|----------------|----------------|----------------|-------------------------------|----------------|---|
| G | B ₃ | B _{max} | B ₁ _{max} | B ₂ | C ₁ | g ₁ | G ₁ | r ₁ _{min} | Excentricity E | Mounting dimension f Min. mm |
| M16 x 1.5 | 15.5 | 19.6 | 52.1 | 32.5 | 0.8 | 6 | 17 | 0.6 | 0.8 | 26 |
| | | | | | | | | | | Maximum operating torque N·m |
| | | | | | | | | | | Basic dynamic load rating C N |
| | | | | | | | | | | Basic static load rating C ₀ N |
| | | | | | | | | | | Maximum allowable static load N |

PRODUCTKENMERKEN

| | |
|----------------|---------------|
| Merk | IKO |
| N° Ean13 | 3616060461117 |
| Binnendiameter | 22 mm |
| Buitendiameter | 35 mm |
| Dikte | 18 mm |
| Gewicht | 193 g |
| Verpakking | 1 |

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE