


Nokrollen CFE24-VUU-IKO - CFE24-VUU-IKO

<https://www.123kogellager.nl/kogellager-behuizing/kogellager/nokrollen/cfe24-vuu-iko>

IKO
CAM FOLLOWERS
Eccentric Type Cam Followers Full Complement Type/With Screwdriver Slot



CFE24-VUU

Outside diameter of eccentric roller mm	Identification number				Mass (Ref.) g	D	C	d _e
	Shield type		Sealed type					
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring				
33				CFE 24 VUU	900	62	29	33

Boundary dimensions mm														
G	B ₃	B _{max}	B ₁ _{max}	B ₂	C ₁	g ₁	G ₁	r ₁ _{min}	Excentricity E	Mounting diameter f Min. mm	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N
M24 × 1.5	25.5	30.6	80.1	49.5	0.8	8	24	1	0.8	40	215	46 800	92 000	52 000

PRODUCTKENMERKEN

Merk	IKO
N° Ean13	3616060461254
Binnendiameter	33 mm
Buitendiameter	62 mm
Dikte	29 mm
Gewicht	900 g
Verpakking	1

contact@123kogellager.nl

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE